### UNITED STATES PATENT AND TRADEMARK OFFICE **CERTIFICATE OF CORRECTION**

Page 1 of 10

PATENT NO. : 6,889,965 B2 **APPLICATION NO. : 09/974991** 

DATED INVENTOR(S) : May 10, 2005 : Robert T. Loftus et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

The title page should be deleted and substitute therefore the attached title page.

Drawings:

Delete drawing sheets 1-8, and substitute therefore the drawing sheets, consisting of Figs. 1-8.

# (12) United States Patent

Loftus et al.

(10) Patent No.:

US 6,889,965 B2

(45) Date of Patent:

May 10, 2005

## (54) OPPOSING CONICAL PRELOADED ELASTOMERIC BEARING ASSEMBLY

- (75) Inventors: Robert T. Loftus, Gilbert, AZ (US); Neal M. Muylaert, Apache Junction, AZ (US)
- (73) Assignee: The Boeing Company, Chicago, IL (US)
- (\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 114 days.
- (21) Appl. No.: 09/974,991
- (22) Filed: Oct. 10, 2001
- (6S) Prior Publication Data
  US 2003/0068104 A1 Apr. 10, 2003

(51)	Int. Cl.7 F16M 1/00
(52)	U.S. Cl
	Kield of Search 416/134 A. 191.

416/244 R, 244 B, 106, 107, 160, 135; 384/221; 267/136

#### (56) References Cited

#### U.S. PATENT DOCUMENTS

		Julien	267/33
3,782,854 A		Rybicki	
3,862,812 A		Goradt et al.	
4,028,002 A	6/1977	Finney et al.	

4,129,403 A 4,297,078 A 4,306,836 A 4,341,499 A	• 10/1981	Watson	416/134 A
4,365,936 A 4,859,148 A 5,601,408 A 6,413,048 B1			416/134 A

#### \* cated by examiner


Primary Examiner—Robert A. Siconolfi Assistant Examiner—Melanic Torres

(74) Attorney, Agent, or Firm-Black Lowe & Graham PLLC

#### (57) ABSTRACT

The invention provides a weight-reducing bearing assembly for rotary aircraft. An opposed tapered conical elastomeric flap bearing assembly for rotary aircraft includes an outer housing having an outer surface and an inner surface. The outer surface is configured to mechanically connect the bearing assembly to the attachment sections of the hub center body. The inner surface is configured to receive a pair of opposed taper conical bearing elements. An inboard bearing element and an outboard bearing element are located within the outer housing. The bearing elements are arranged in an opposed manner. An axial pre-load can be applied to the opposed bearing assembly wherein the resulting force couple bearing pre-load path is maintained entirely within the bearing assembly. Consequently, the weight of the main rotor hub is reduced increasing the efficiency of rotary flight.

#### 20 Claims, 6 Drawing Sheets



### UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

PATENT NO.

: 6,889,965 B2

Page 3 of 10

APPLICATION NO.: 09/974991

: May 10, 2005

INVENTOR(S)

: Robert T. Loftus et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

```
at col. 1, line 45, please replace "20aincludes" with -- 20a includes --;
at col. 1, line 48, please delete "52";
at col. 2, line 37-38, please replace "is a" with -- shows --, and please replace "view of a
bearing assembly" with -- views of bearing assemblies --;
at col. 2, line 39, please replace "isometric" with -- cross sectional --;
at col. 2, line 42, please replace "an isometric" with -- a cross sectional --;
at col. 3, line 3, after "30b", please insert --, as shown in FIG. 3A, --;
at col. 3, line 10, please replace "yolk" with -- yoke --;
at col. 3, line 16, after "projections" please insert --, (e.g. bearing assembly 30c shown
in FIG. 3B), --;
at col. 3, line 17, please replace "yolk" with -- yoke --;
at col. 3, line 20, please replace "3" with -- 3A --, and please replace "an isolated" with
-- a partial sectional isolated plan --;
at col. 3 line 23, please replace "yolk" with -- yoke --;
at col. 3, line 34, after "exploded" please insert -- cross sectional --;
at col. 3, line 41, please replace "yolk" with -- yoke -- and please replace "FIG. 1" with
-- FIGS. 2 and 3A --;
at col. 3, line 60, please replace "the proximal" with -- inner bearing --;
at col. 3, line 61, please replace "section 65" with -- element 32 --;
at col. 4, line 9, please replace "65" with -- 53 --;
```

at col. 4, line 10, please replace "29 (FIG. 1)" with -- 28 (FIG. 2) --;

at col. 4, line 11, please replace "an assembled" with -- a cross sectional --;

# UNITED STATES PATENT AND TRADEMARK OFFICE **CERTIFICATE OF CORRECTION**

PATENT NO. : 6,889,965 B2 Page 4 of 10

APPLICATION NO.: 09/974991

DATED: May 10, 2005

INVENTOR(S): Robert T. Loftus et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

at col. 4, line 15, please replace "42 encompasses" with -- 42b encompasses --;

at col. 4, line 20, please replace "assembly" with -- element --;

at col. 4, line 22, after "race" please insert -- 66 --, please replace "baring 66" with

--bearing --, and after "surface" please insert -- 67 --;

at col. 4, line 27, after "bore" please insert -- 46 --;

at col. 4, line 29, please replace "29" with -- 28 --, and please replace "1" with -- 2 --;

at col. 4, line 30, please delete "58";

at col. 4, line 32, please replace "29" with -- 28 --;

at col. 4, line 33, please delete "to"; and

Signed and Sealed this

Twenty-sixth Day of December, 2006

JON W. DUDAS
Director of the United States Patent and Trademark Office

May 10, 2005

Sheet 1 of 6

6,889,965 B2




Fig. 1.

May 10, 2005

Sheet 2 of 6

6,889,965 B2






Fig. 2.





May 10, 2005

Sheet 5 of 6

6,889,965 B2




Fig. 6.

May 10, 2005

Sheet 6 of 6

6,889,965 B2

